



Pipe Lifting Clamp TPH/TPH-HD

Product information

Heavy duty clamp with high pressure resistant plastic for horizontal pipe lifting. Clamp for horizontal lifting and transporting of steel and concrete pipes without damaging the product.

Model THP: Standard clamp

Model THP-HD: special for extreme heavy duty lifting situations

Features:

- TPH Jaw is covered with a special high quality pressure resistant plastic.
- TPH-HD Jaw is covered with special high quality extreme high pressure resistant plastic.
- Maintenance-friendly clamps, plastic pressure resistant cover is easy to change.
- TPH-HD has special handle for easy handling.
- Compact design and high lifting capacity.
- Lightweight design for easy handling.
- Tough quality heavy duty body.

Marking: According to standard, CE-marked, Type, serial number, WLL, Jaw opening

Temperature range: TPH: - 40°C to + 50°C. / TPH-HD - 30°C to + 80°C.

Standard: EN 13155

Note: Must always be used in pairs

| Part code | Code | WLL ton | Jaw width mm | V mm | S mm | W mm | U mm | T mm | X mm | Y mm | Weight kg |
|-----------------|---------|---------|--------------|------|------|------|------|------|------|------|-----------|
| 502100150400740 | 1.5 TPH | 1.5 | 40 | 120 | 70 | 50 | 185 | 16 | 41 | 25 | 2 |
| 502100300400740 | 3 TPH | 3 | 40 | 120 | 70 | 50 | 185 | 16 | 41 | 25 | 2 |
| 502100400500740 | 4 TPH | 4 | 50 | 140 | 70 | 58 | 204 | 26 | 41 | 25 | 3 |
| 502100600500740 | 6 TPH | 6 | 50 | 140 | 70 | 58 | 204 | 26 | 41 | 25 | 3 |
| 502100800700740 | 8 TPH | 8 | 70 | 140 | 70 | 58 | 224 | 26 | 45 | 25 | 3.4 |
| 502101000700740 | 10TPH | 10 | 70 | 140 | 70 | 58 | 224 | 26 | 85 | 45 | 5 |
| 502101200700740 | 12TPH | 12 | 70 | 140 | 70 | 58 | 224 | 26 | 85 | 45 | 7 |
| 502101500700740 | 15TPH | 15 | 70 | 155 | 70 | 76 | 250 | 26 | 100 | 60 | 9 |
| 502102000700740 | 20TPH | 20 | 70 | 155 | 70 | 76 | 250 | 26 | 100 | 60 | 9 |

Blueprint

