



Eye Nut EL, Green Pin®

Product information



Certification: at no extra charge this product can be supplied with a works certificate, a 3.1 material certificate and/or EC Declaration of Conformity

Material: alloy steel, quenched and tempered

Marking: CE-marked

Temperature range: -40°C up to +200°C

Finish: Painted red or white

Safety factor: 5:1

Grade: 8

Part Code	Diameter mm	WLL ton	Diameter thread a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	Weight kg
11.40EL6R	11	0.2	M6 x 1.00	31	51	30	14	44	6	6	0.15
11.40EL8R	11	0.4	M8 x 1.25	31	51	30	14	44	11	6	0.15
11.40EL10R	11	0.7	M10 x 1.50	31	51	30	14	44	11	6	0.15
11.40EL12R	12	1	M12 x 1.75	39	56	32	15	48	12	6	0.23
11.40EL14R	12	1.2	M14 x 2.00	39	56	32	15	48	12	6	0.23
11.40EL16R	14	1.5	M16 x 2.00	44	65	37	16	60	14	8	0.4
11.40EL18R	14	2	M18 x 2.50	44	65	37	16	60	14	8	0.4
11.40EL20R	14	2.5	M20 x 2.50	44	65	37	16	60	14	8	0.4
11.40EL22R	16	3	M22 x 2.50	52	80	48	21	75	16	11	0.63
11.40EL24R	16	4	M24 x 3.00	52	80	48	21	75	16	11	0.63
11.40EL27R	16	5	M27 x 3.00	52	80	48	21	75	16	11	0.63
11.40EL30R	21	6	M30 x 3.50	66	96	58	25	88	21	14	1.11
11.40EL33R	21	7	M33 x 3.50	66	96	58	25	88	21	14	1.11
11.40EL36R	25	8	M36 x 4.00	84	121	73	39	100	25	17	2.22
11.40EL39R	25	9	M39 x 4.00	84	121	73	39	100	25	17	2.22
11.40EL42R	25	10	M42 x 4.50	84	121	73	39	100	25	17	2.22
11.40EL45R	25	15	M45 x 4.50	90	132	82	42	121	25	22	2.73
11.40EL48R	25	18	M48 x 5.00	90	132	82	42	121	25	22	2.73

Blueprint

