



Heavy Duty Shackle Green Pin® P-6036

Product information



Bow shackles with safety bolt.

Certification: This product can be supplied with a works certificate, 3.1 material certificate, manufacturer test certificate, EC Declaration of Conformity. All shackles starting from 150 tons are supplied with a Lloyd's Register of Shipping Certificate on proof load.

Material: Bow and pin alloy steel, Grade 8 quenched and tempered.

Finish: Shackle bow painted silver, pin painted green (120 tons shackle is hot dipped galvanized).

Note: This shackle can also be delivered with fixed nut (an extra AISI 316 securing bolt is drilled through both the nut and shackle pin. This securing bolt is fastened with two sets of Nord-Lock®)

Safety factor: 5:1

Grade: 8

Part Code	WLL ton	A mm	B mm	C mm	D mm	e mm	f mm	g mm	h mm	i mm	j mm	k mm	Weight kg
11.31HDGPHM0120	120	95	95	208	91	147	400	238	647	440	428	50	110
11.31HDGPHM0150	150	105	108	238	102	169	410	275	688	490	485	60	160
11.31HDGPHM0200	200	120	130	279	113	179	513	290	838	520	530	60	235
11.31HDGPHM0250	250	130	140	299	118	205	554	305	904	560	565	65	285
11.31HDGPHM0300	300	140	150	325	123	205	618	305	996	575	585	70	340
11.31HDGPHM0400	400	170	175	376	164	231	668	325	1,114	690	665	70	560
11.31HDGPHM0500	500	180	185	398	164	256	718	350	1,190	720	710	70	685
11.31HDGPHM0600	600	200	205	444	189	282	718	375	1,243	810	775	70	880
11.31HDGPHM0700	700	210	215	454	204	308	718	400	1,263	870	820	70	980
11.31HDGPHM0800	800	210	220	464	204	308	718	400	1,270	870	820	70	1,100
11.31HDGPHM0900	900	220	230	485	215	328	718	420	1,296	920	860	70	1,280
11.31HDGPHM1000	1,000	240	240	515	215	349	718	420	1,336	940	900	70	1,460
11.31HDGPHM1250	1,250	260	270	585	230	369	768	450	1,456	1,025	970	70	1,990
11.31HDGPHM1500	1,500	280	290	625	230	369	818	450	1,556	1,025	1,010	70	2,400

Blueprint

