



Sling Shackle P-6033

Product information

Bow shackles with safety bolt.

Certification: This product can be supplied with a works certificate, 3.1 material certificate, manufacturer test certificate, EC Declaration of Conformity and all shackles from 75 t and up are supplied with a Lloyd's Register of Shipping Certificate on proof load. For shackles 75 t and up an MPI and/or US inspection certificate can be supplied on request.

This shackle can also be delivered with fixed nut (an extra AISI 316 securing bolt is drilled through both the nut and shackle pin. This securing bolt is fastened with two sets of Nord-Lock[®] washers and a securing nut. These washers lock when subjected to movement and keep the nut safely in position).

Material: Bow and pin alloy steel, quenched and tempered

Marking: CE-marked

Temperature range: -20°C up to +200°C

Finish: Shackle bow painted silver, pin painted green

Note: for details on dimensions and tolerances please consult our CAD drawings, these are available on request

Safety factor: 5:1

Grade: 8

Part Code	WLL ton	A mm	B mm	C mm	D mm	e mm	f mm	g mm	h mm	i mm	j mm	k mm	l mm	Weight kg
11.34SLGPF0007	7	22	22	46	19	32	96	64	153	115	110	19	41	2
11.34SLGPF0012	12.5	28	28	61	25	44	121	82	197	151	146	24	54	4
11.34SLGPF0018	18	35	35	69	30	52	148	102	239	175	180	29	64	7
11.34SLGPF0030	30	40	42	90	35	69	165	126	279	211	200	34	79	13
11.34SLGPF0040	40	55	51	109	45	84	199	140	331	252	235	38	97	21
11.34SLGPF0055	55	60	57	115	55	90	240	160	389	299	270	45	100	30
11.34SLGPF0075	75	68	70	125	54	110	290	185	473	327	317	54	120	48
11.34SLGPF0125	125	85	80	154	85	137	366	220	583	426	390	64	150	92
11.34SLGPF0150	150	94	95	179	89	147	391	253	645	435	434	50	170	140
11.34SLGPF0200	200	110	105	199	100	158	481	280	759	470	482	50	205	205
11.34SLGPF0250	250	126	120	227	110	179	542	300	859	519	530	60	240	264
11.34SLGPF0300	300	135	134	245	122	195	601	350	947	575	620	70	265	360
11.34SLGPF0400	400	160	160	293	145	231	576	370	985	675	690	80	320	580
11.34SLGPF0500	500	170	180	328	160	263	681	450	1.131	748	790	90	339	780
11.34SLGPF0600	600	190	200	348	170	289	741	490	1.234	809	865	100	370	980
11.34SLGPF0700	700	200	215	392	190	315	751	540	1.284	879	901	100	400	1,360
11.34SLGPF0800	800	218	230	420	200	342	851	554	1.426	942	947	110	420	1,430
11.34SLGPF0900	900	242	255	466	220	368	851	580	1.488	1.023	1.023	120	440	1,650
11.34SLGPF1000	1,000	260	270	490	240	399	851	614	1.532	1.103	1.107	120	460	2,970
11.34SLGPF1250	1,250	285	300	510	260	452	931	650	1.666	1.227	1.182	150	530	3,700
11.34SLGPF1550	1,550	285	320	550	280	483	950	680	1,710	1,300	1.253	150	560	4,000

Blueprint

