



Dynamometer Tractel dynafor™ Industrial

Product information

Rugged and lightweight wireless digital dynamometer. Integrated LCD screen with 18 mm high digits for good readability. With indication of battery discharge status. With tare, peak hold and units change (kg, daN, lbs), automatic zeroing, automatic stop without load or variation (20 min.).

Specifications:

- Capacity range from 1 t up to 20 t
- $\pm 0.3\%$ accuracy of measuring range
- Battery life: 350 h
- Uses 2 x AAA batteries

Protection class: IP65

Material: Steel, aluminium

Temperature range: -20°C up to +50°C

| Part Code | WLL ton | A mm | B mm | C mm | D mm | E mm | F mm | G mm | H mm | Weight kg |
|-------------|---------|------|------|------|-------|------|------|------|------|-----------|
| 16.50260889 | 1 | 191 | 164 | 22 | 83.5 | 22 | 19.8 | 36.4 | 37.6 | 0.75 |
| 16.50260899 | 3.2 | 191 | 164 | 22 | 99.5 | 22 | 19.8 | 36.4 | 44.8 | 0.93 |
| 16.50260909 | 6.3 | 236 | 184 | 28 | 121.5 | 22 | 19.8 | 36.4 | 54.7 | 1.44 |
| 16.50260919 | 12.5 | 277 | 226 | 42 | 120.5 | 45 | 40.5 | 59.4 | 60 | 3.22 |
| 16.50260929 | 20 | 342 | 264 | 54 | 147 | 45 | 40.5 | 59.4 | 73.5 | 5.1 |

Blueprint

