



Hydraulic crimping tool

Product information

General: Hydraulic one-hand operated electric crimping tool for steel wire ropes in lightening arrangements, rigging, marine ropes, theatres, exhibitions and other applications. Quick change of die sets, rotating crimping head, delivered in a case with a place for set of dies (not included) and charger.

Pressforce: 35 kN (3600 kp)

Weight: 2,1 kg

Dimensions: 128x75x340 mm

Standard dies: Length 8,75/6,3 mm

Accessory: Press dies length 12 mm

| Part Code | Code | Weight kg |
|-------------|--------|--------------|
| 10.47BPL031 | BPL031 | 2.1 |

Technical data

| Art No | Code | Steel wire rope Ø | Steel wire rope Ø | Ferrule* | Number of presses/ferrule | | |
|-------------|---------|-------------------|-------------------|----------|---------------------------|-------------|-----------|
| | | fiber core | steel core | no | Die 6,3 mm | Die 8,75 mm | Die 12 mm |
| | | mm | mm | | pc | pcs | pcs |
| 10.47MK3115 | MK31.15 | 1,1-1,5 | 0,9-1,1 | 1,5 | - | 1 | - |
| 10.47MK3120 | MK31.20 | 1,6-2 | 1,2-1,6 | 2 | - | 2 | 1 |
| 10.47MK3125 | MK31.25 | 2,1-2,6 | 1,7-2,1 | 2,5 | - | 2 | 1 |
| 10.47MK3130 | MK31.30 | 2,7-3,1 | 2,2-2,6 | 3 | - | 2 | 1 |
| 10.47MK3135 | MK31.35 | 3,2-3,6 | 2,7-3,1 | 3,5 | - | 2 | 2 |
| 10.47MK3140 | MK31.40 | 3,7-4,1 | 3,2-3,6 | 4 | - | 3 | 2 |
| 10.47MK3145 | MK31.45 | 4,2-4,6 | 3,7-4,2 | 4,5 | 4 | - | - |
| 10.47MK3150 | MK31.50 | 4,7-5,1 | 4,3-4,6 | 5 | 4 | - | - |
| 10.47MK3160 | MK31.60 | 5,2-6,1 | 4,7-5,5 | 6 | 5 | - | - |