



Chain Coupler Crosby S-1325A

Product information

Features:

- Locking system that provides for simple assembly and disassembly – no special tools required.
- Designed to connect Grade 100 chain fittings produced with “Engineered Flat” to Grade 100 chain.
- Suitable for use with Grade 100 and Grade 80 chain.
- Individually Proof Tested to 2-1/2 times the Working Load Limit with certification.
- Fatigue rated at 1-1/2 times the Working Load Limit at 20,000 cycles.

Material: Forged Alloy Steel - Quenched and Tempered.

Marking: Chain size, code and grade.

Finish: Painted.

Safety factor: 4:1

Grade: 10

| Part code | Code | Chain diameter mm | WLL ton | C, | F, | G, | Weight kg |
|--------------|---------------|----------------------|------------|------|------|------|--------------|
| 402200150010 | S-1325A-6-10 | 6 | 1.5 | 26.2 | 19.3 | 44.7 | 0.11 |
| 402200200010 | S-1325A-7-10 | 7 | 2 | 35.8 | 22.4 | 59 | 0.23 |
| 402200250010 | S-1325A-8-10 | 8 | 2.5 | 35.6 | 22.4 | 59 | 0.23 |
| 402200400010 | S-1325A-10-10 | 10 | 4 | 46.7 | 30 | 69 | 0.34 |
| 402200680010 | S-1325A-13-10 | 13 | 6.8 | 55.6 | 38.1 | 94.5 | 0.75 |
| 402201030010 | S-1325A-16-10 | 16 | 10.3 | 71.4 | 49.8 | 112 | 0.86 |

Blueprint

