



Wireless Loadshackle

Product information

Wireless loadshackle with low headroom and a load-centering bobbin.

Battery type/life: Loadcell 4 x AA Alkaline/Load cell 1200 hours continuous.

Accuracy: $\pm 1\%$ of applied load.

Frequency: 2.4 GHz.

System range: 700 m.

Data rate: 3 updates per second.

Protection: IP67.

Temperature range: -10°C up to $+50^{\circ}\text{C}$.

Note: Safety factor when used with a load bobbin.

Safety factor: 5:1

Part Code	Code	WLL ton	Resolution T	A mm	ØB	C mm	D mm	E mm	H mm	L mm	N mm	P mm	Weight kg
16.50WLS3,25T	WLS3,25T	3.25	5	26.9	19.1	56.9	16	42.9	106	127.1	17.5	143	2.8
16.50WLS6,5T	WLS6,5T	6.5	5	36.6	25.4	79.7	22.4	58	148	156.5	24.6	173	3.2
16.50WLS12T	WLS12T	12	10	51.5	35.1	113	31.8	82.5	210	196	35.1	218	8
16.50WLS25T	WLS25T	25	20	73	51	170	44.5	127	313	281	57	293	18
16.50WLS55T	WLS55T	55	50	82.5	57	189.5	51	164	348	306	61	317	25
16.50WLS85T	WLS85T	85	50	105	70	253	66.5	184	453	368	79	394	45
16.50WLS120T	WLS120T	120	100	127	82.5	319.5	76	200	546	408	92	441	85
16.50WLS200T	WLS200T	200	200	180	125	483	120	290	810	580	120	565	254
16.50WLS300T	WLS300T	300	500	205	150	576	130	305	950	615	130	615	374
16.50WLS400T	WLS400T	400	500	230	175	650	165	325	1,100	705	165	711	614

Blueprint

