



Crane Dynamometer V-LINK

Product information

Digital dynamometer with high efficiency and precision in all environments. The dynamometer is also ideal for wet, humid and harsh environments. Fast charging with standard USB charger. LED display is visible at long distances with big, red digits. With peak hold function, tare function and channel selection.

Specifications:

Accuracy: $\pm 0,2\%$
 Safe overload: 110%
 IP Class: IP67
 Display: Bright LED
 Digit height: 14 mm
 Digit colour: Red
 Operating time: 16-20 hours (Low temperature will decrease the operating time)
 Batteries: Built-in Li-on
 Charger: High quality USB charger

Accessory options:

Wireless remote display (purchased separately, Art No.: 16.502000B-6V-RTX)

Material: High strength steel housing.

Temperature range: -20°C up to +50°C.

Finish: Fe/Zn12 chromite surface treatment according to ISO 2081.

Safety factor: 5:1

Part Code	WLL ton	Increment kg	A mm	B mm	C mm	D mm	E mm	Ø mm	Weight kg
16.50670601	6.5	5	200	115	117	260	41,5	31	4.47
16.50671201	12	10	200	115	117	281	41,5	37,3	5.65
16.50672501	25	10	230	115	117	338	41,5	54	7.56
16.50675501	55	50	282	115	155	440	46	73	16.93

Blueprint

