

## **Beam Clamp POWERTEX PBC-S1**

## **Product information**





POWERTEX Beam Clamp PBC-S1 is durable and easy to install on different beam types. The beam clamp is designed to provide quick rigging and hoisting points for a great variety of applications.

## Features:

- Safe All POWERTEX Beam Clamps are proof load tested 2 x WLL
- Compact, lightweight construction
- Low headroom design
- Durable all steel construction with powder coated finish and black plated spindle and grip
- RFID equipped (chip) for easy service and inspection
- QR code for on-site access to Multilanguage user manuals
- Test certificate and Declaration of Conformity enclosed with each beam clamp
- Can be turned into Blackline version by adhering the included grey label over the shiny nameplate

Blackline products are suitable for use in theatres and the entertainment industry.

Marking: According to standard, CE-marked, POWERTEX, Model, WLL, Serial number, QR code

Temperature range: -10°C up to +50°C.

Finish: Black powder coating.

Standard: EN 13155

Safety factor: 4:1.

Part code	Code	WLL ton	Beam width	A max mm	B min mm	B max mm	C mm	D mm	E mm	H mm	F min mm	F max mm	G min mm	Weight kg
502300102400040	1t PBC	1	80-240	270	183	370	94	4	198	20	100	154	22	3.5
502300202400040	2t PBC	2	80-240	270	183	370	102	6	198	20	100	154	22	4.5
502300303300040	3t PBC	3	90-330	355	243	500	132	8	263	22	148	219	46	9.5
502300503300040	5t PBC	5	90-330	355	243	500	142	10	263	28	148	219	43	11
502301003500040	10t PBC	10	90-350	364	269	521	180	12	285	38	165	239	51	16

## Blueprint

