



## Wire Rope Polyamide/Nylon-coated 6x19M-WSC

### Product information



A galvanized rope equipped with a Wire Strand Core (WSC) and has a Transparent polyamide/nylon coating. It can be a good choice for basic lifting applications such as lifting slings, security rope in studios/theaters premises, etc.

**Rope construction:** 6x19M-WSC

**Marking:** According to standard

**Temperature range:** App. +120°C

**Finish:** Polyamide/Nylon-coated

**Standard:** EN 12385-4

*except from coating*

**Fill factor:** 0,53

General use



Slings



Part Code	Rope Diameter, mm	Inner diameter mm	Tensile strength N/mm <sup>2</sup>	Steel area mm <sup>2</sup>	Min. Breaking force kN.	Colour	Weight kg/100m
105130350250264	3.5	2.5	1,770	2.61	4	Black	3
105130400300264	4	3	1,770	3.76	5.77	Black	4
105130450300264	4.5	3	1,770	3.76	5.77	Black	4
105130500330260	5	3.3	1,770	4.55	6.98	transparent	4.8
105130500330264	5	3.3	1,770	4.55	6.98	Black	4.8
105140500330260	5	3.3	1,960	4.55	7.73	transparent	4.8
105130500350260	5	3.5	1,770	5.12	7.85	transparent	5
105130600450260	6	4.5	1,770	8.46	13	transparent	8.9
105130600450264	6	4.5	1,770	8.46	13	Black	8.9
105140600450260	6	4.5	1,960	8.46	14.4	transparent	8.9
105130700530260	7	5.3	1,770	11.7	18	transparent	12
105140700530260	7	5.3	1,960	11.7	19.9	transparent	12
105130800630260	8	6.3	1,770	16.6	25.4	transparent	17
105140800630260	8	6.3	1,960	16.6	28.2	transparent	17
105131000800260	10	8	1,770	287	41	transparent	29
105141000800260	10	8	1,960	16.6	45.4	transparent	29