



## Wire Rope Polyamide/Nylon-coated 6x19M-WSC

### Product information



A galvanized rope equipped with a Wire Strand Core (WSC) and has a Transparent polyamide/nylon coating. It can be a good choice for basic lifting applications such as lifting slings, security rope in studios/theaters premises, etc.

**Rope construction:** 6x19M-WSC

**Marking:** According to standard

**Temperature range:** App. +120°C

**Finish:** Polyamide/Nylon-coated

**Standard:** EN 12385-4

*except from coating*

**Fill factor:** 0,53

General use



Slings



Part code	Rope diameter mm	Inner diameter mm	Colour	Tensile strength N/mm <sup>2</sup>	Min. breaking force kN	Steel area mm <sup>2</sup>	Lubrication	Weight kg/100m
105130350250264	3.5	2.5	Black	1,770	4	2.61	-	3
105130400300264	4	3	Black	1,770	5.77	3.76	-	4
105130450300264	4.5	3	Black	1,770	5.77	3.76	-	4
105130500330260	5	3.3	transparent	1,770	6.98	4.55	-	4.8
105130500330264	5	3.3	Black	1,770	6.98	4.55	-	4.8
105140500330260	5	3.3	transparent	1,960	7.73	4.55	-	4.8
105130500350260	5	3.5	transparent	1,770	7.85	5.12	-	5
105130600450260	6	4.5	transparent	1,770	13	8.46	-	8.9
105130600450264	6	4.5	Black	1,770	13	8.46	-	8.9
105140600450260	6	4.5	transparent	1,960	14.4	8.46	-	8.9
105130700530260	7	5.3	transparent	1,770	18	11.7	-	12
105140700530260	7	5.3	transparent	1,960	19.9	11.7	-	12
105130800630260	8	6.3	transparent	1,770	25.4	16.6	-	17
105140800630260	8	6.3	transparent	1,960	28.2	16.6	-	17
105131000800260	10	8	transparent	1,770	41	287	-	29
105141000800260	10	8	transparent	1,960	45.4	16.6	-	29