

Multifunction Lifting Beam X-lift 900



Product information

General: Automatically adjusts to the width of the load, load lays undamaged. Length can be adjusted. Load stays balanced during lifting. Light weight, when folded fits small space and is easy to handle.

Lifting beams are made on an individual order.

Material: High-strength structural steel

Marking: WLL and CE-marking

Finish: Yellow painted

Note: Extension beams and accessories available

Part Code	WLL ton	Model	Length mm L min	Length mm L max	WLL ton 60°	WLL ton 45°	Transport measures Height mm	Transport measures Width mm	Extension beams pcs	t mm	Weight kg
13.359003425	3	900-3-4.25	2,450	4,250	1,5	3	320	170	1	3	83
13.3590010425	10	900-10-4.25	2,450	4,250	5	10	365	195	2	10	143
13.359001062	10	900-10-6.2	3,500	6,200	5	10	365	195	1	10	185
13.35900585	10	900-5-8.5	4,900	8,500	-	5	365	195	-	10	264
13.3590020425	20	900-20-4.25	2,450	4,250	10	20	460	240	2	20	326
13.359002062	20	900-20-6.2	3,500	6,200	10	20	460	240	1	20	430
13.359002085	20	900-20-8.5	4,900	8,500	-	20	460	240	-	20	570
13.3590030425	30	900-30-4.25	2,450	4,250	15	30	535	265	2	30	429
13.359003062	30	900-30-6.2	3,500	6,200	15	30	535	265	1	30	555
13.359003085	30	900-30-8.5	4,900	8,500	-	30	535	265	-	30	720
13.3590050425	50	900-50-4.25	3,270	4,470	-	50	740	480	3	30	647
13.359005051	50	900-50-5.1	3,520	5,320	-	50	740	480	3	30	754
13.359005062	50	900-50-6.2	4,020	6,420	-	50	740	480	3	30	878
13.359005085	50	900-50-8.5	5,120	8,720	-	50	740	480	2	30	1,071