

Lifting Eye Nut DIN 582 Electro Galvanized

Product information



Material: Steel C15E

Marking: According to standard, WLL, manufacturer C15, thread & CE

Finish: Electro galvanized.


Standard: DIN 582

Warning: The lifting eyes shall be screwed tight against the surface. When two lifting eyes are used their mutual position shall result in the two eyes at the same level. Larger angle between the slings than 90° are not tolerated. Lifting eyes can not be assembled against a surface that differ essentially from a surface perpendicular to the direction of the lift.

Safety factor: 6:1

Lifting Eye Nut DIN 582 Electro Galvanized

Blueprint



Technical data

| Part code | WLL ton | Thread | d1 mm | d2 mm | d3 mm | d4 mm | h mm | k mm | Weight kg/100pc |
|--------------|---------|--------|-------|-------|-------|-------|------|------|-----------------|
| 421100010070 | 0.14 | M8 | M8 | 20 | 36 | 20 | 36 | 8 | 5 |
| 421100020070 | 0.23 | M10 | M10 | 25 | 45 | 25 | 45 | 10 | 9 |
| 421100030070 | 0.34 | M12 | M12 | 30 | 54 | 30 | 53 | 12 | 16 |
| 421100070070 | 0.7 | M16 | M16 | 35 | 63 | 35 | 62 | 14 | 24 |
| 421100120070 | 1.2 | M20 | M20 | 40 | 72 | 40 | 71 | 16 | 36 |
| 421100180070 | 1.8 | M24 | M24 | 50 | 90 | 50 | 90 | 20 | 72 |
| 421100320070 | 3.2 | M30 | M30 | 65 | 108 | 60 | 109 | 24 | 132 |
| 421100460070 | 4.6 | M36 | M36 | 75 | 126 | 70 | 128 | 28 | 208 |
| 421100630070 | 6.3 | M42 | M42 | 85 | 144 | 80 | 147 | 32 | 311 |
| 421100860070 | 8.6 | M48 | M48 | 100 | 166 | 90 | 168 | 38 | 502 |