

Wall Jib Crane Underbraced 180° PMI

Product information

The headroom is the main asset of the PMI. Its I beam profile allows to consider installation of a hoist with electric or manual steering.

The PMT are delivered with standard mounting brackets and our mounting kits KITFIX (optional) ensure safe anchorages for specific supports.

A full range of accessories is available.

Options

- Hoist power supply cable + lockable main switch
- Standpipe
- Rotation slowing device (adaptable without welding or mechanical intervention)
- Hot dip galvanizing (contact us)
- Rotation stops to weld onto the assembly
- Single or multipositions rotation lock
- Outdoor use
- Motorization
- Electric or manual hoist

[... Read more](#)



Wall Jib Crane Underbraced 180° PMI

Technical data

| Part code | WLL ton | Length m | Cap. kg |
|-----------------|------------|-------------|------------|
| 6025PMI00152000 | 0.15 | 2 | 150 |
| 6025PMI00252000 | 0.25 | 2 | 250 |
| 6025PMI00502000 | 0.5 | 2 | 500 |
| 6025PMI01002000 | 1 | 2 | 1,000 |
| 6025PMI01602000 | 1.6 | 2 | 1,600 |
| 6025PMI02002000 | 2 | 2 | 2,000 |
| 6025PMI02502000 | 2.5 | 2 | 2,500 |
| 6025PMI03202000 | 3.2 | 2 | 3,200 |
| 6025PMI04002000 | 4 | 2 | 4,000 |