



## Round Sling EXTREEMA® XS

### Product information

The XS round slings are the ultimate solution for lifting loads ranging from 1T to 20T. They offer a cost-effective and reliable alternative to traditional polyester slings. Say goodbye to the hassle of disposal, storage, and transportation costs, and welcome a practical and efficient choice that never compromises safety and quality.

Their lightweight design ensures easy handling and transport, making them a practical choice across various lifting applications. By embracing the XS round slings, industries secure a dependable lifting solution and embark on a sustainable journey, reducing industrial waste and minimizing their environmental footprint.

Extreema XS Slings have massive lifting power in a much smaller size with 78% less weight than polyester round slings and 55% smaller diameter, you can lift on the shackle pin. Slings are 8-10 times lighter than steel wire ropes.

#### Features and benefits:

- Saving costs
- D:d ratio of 1:1
- Environmentally friendly
- Light in weight
- Flexible
- Less storage
- Long life cycle
- Access to limited lifting space
- Safer lifting operations
- Improving workflow
- Available in 3t yellow, 5t red, 10t orange, 15t orange and 20t orange
- Available in effective working lengths in the range of 0.5 m up to 16 m

**Material:** HMPE -Dyneema®

**Marking:** According to standard, CE-marked

**Temperature range:** -50°C up to +70°C

**Standard:** EN 1492-2

*except material*

**Safety factor:** 7:1

Part Code	WLL ton
340500300050030	3
340500300080030	3
340500300100030	3
340500300150030	3
340500300200030	3
340500300250030	3
340500300300030	3
340500300400030	3
340500300500030	3
340500500050030	5
340500500100030	5
340500500150030	5
340500500200030	5
340500500250030	5
340500500300030	5
340500500400030	5
340500500500030	5
340501000150030	10
340501000200030	10
340501000300030	10
340501000400030	10
340501000500030	10

Technical data

<b>Extreema® XS roundsling</b>				
<b>HMPE EXS</b>				
<b>WLL</b>	<b>SF</b>	<b>Core ø mm</b>	<b>Weight kg 3m EWL</b>	<b>p/m extra kg</b>
3t	7	9	0,8	0,25
5t	7	14	1,35	0,43
10t	7	23	2	0,65
15t	7	31	3,5	1,15
20t	7	37	4,6	1,50