Lifting Solutions Group
Axel Johnson International

Fall Arrest Block IKAR HWPB with Webbing

Product information



Robust, low-maintenance fall arrest device with webbing and swivel. The swivel prevents the webbing from twisting. Internal energy-absorber and hook with fall indicator.
Low weight thanks to extra light plastic housing.

Approved for vertical and horizontal use.

Edge tested: Tested at sharp edges, R ≥ 0,5 mm (CNB/P/11.060 2008 sharp edge Type A)
Carabiner: IKAR Small swivel snap hook IKV11 (L_k = 136,5 mm -opening Ø 25 mm).

The blocks can also be delivered with the following approvals: ANSI/ASSE Z 359.14-2014/LE up on request.

... *Read more*


Material: Body: plastic, webbing: Dyneema®
Marking: According to standard, CE-mark
Temperature range: -40ºC to +50ºC.
Standard: EN 360

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Fall Arrest Block IKAR HWPB with Webbing

Blueprint



Technical data

Part code	Code	Max. number of persons	Length m	Max load kg	Dimensions mm	L mm	B mm	T mm	Lk mm	Lk mm	Lk mm	Weight kg
822100350630	HWPB 3.5	1	3.5	136	326 x 104 x 78	326	104	78	-	136.5	-	1.2
822100550630	HWPB 5.5	1	5.5	136	300 x 130 x 78	300	130	78	-	-	136.5	1.5
822100700630	HWPB 7	1	7	136	300 x 165 x 80	300	165	80	-	-	136.5	1.8
822100900630	HWPB 9	1	9	136	335 x 168 x 88	355	168	88	-	-	136.5	2.3
822101200630	HWPB 12	1	12	136	370 x 195 x 95	370	195	95	136.5	-	-	3.4
822101500630	HWPB 15	1	15	136	400 x 195 x 95	400	195	95	-	136.5	-	4.8

© November 2026 - All Rights Reserved