



Fall Arrest IKAR HWPB with Webbing

Product information

Robust, low-maintenance fall arrest device with webbing and swivel. The swivel prevents the webbing from twisting. Internal energy-absorber and hook with fall indicator.

Low weight thanks to extra light plastic housing.

Approved for vertical and horizontal use.

Rated load: 136 kg

Edge tested: Tested at sharp edges, $R \geq 0,5$ mm (CNB/P/11.060 2008 sharp edge Type A)

Carabiner: IKAR IKV11 (Lk = 137 mm) Small swivel snap hook (opening \varnothing 25 mm).

The blocks can be delivered with the following approvals: ANSI/ASSE Z 359.14-2014/LE up on request.

Material: Body: Plastic. - Webbing: Dyneema®

Marking: According to standard

Temperature range: -40°C to +50°C.

Standard: EN 360

Part Code	Code	Max. number of persons	Length m	L mm	B mm	T mm	Weight kg
19.0741-HWPB3,5	HWPB 3.5	1	3.5	326	104	78	1.2
19.0741-HWPB5,5	HWPB 5.5	1	5.5	300	130	78	1.5
19.0741-HWPB7	HWPB 7	1	7	300	165	80	1.8
19.0741-HWPB9	HWPB 9	1	9	355	168	88	2.3
19.0741-HWPB12	HWPB 12	1	12	370	195	95	3.4
19.0741-HWPB15	HWPB 15	1	15	400	195	95	4.8

Blueprint

