

## Fall Arrest Block IKAR HWS with Galvanized Wire

---

### Product information



Robust, low-maintenance fall arrest device with galvanized wire and swivel. The swivel prevents the wire from twisting. Internal energy-absorber and hook with fall indicator.

Low weight and maintenance thanks to extra light aluminium housing.

Approved for vertical and horizontal use.

**Edge tested:** Tested at sharp edges,  $R \geq 0,5$  mm (CNB/P/11.060 2008 sharp edge Type A)

**Carabiner:** IKAR IKV21 (Lk = 186mm) small swivel snap hook (opening  $\varnothing$  26 mm)  
Can be delivered with other carabiners or scaffolding hooks up on request.

The blocks can be delivered with the following approvals: ANSI/ASSE Z 359.14-2014/LE up on request.

... [Read more](#)

---

**Material:** Body: Aluminium

**Marking:** According to standard, CE-marked


**Temperature range:** -40°C up to +50°C.

**Finish:** Blue painted

**Standard:** EN 360

## Fall Arrest Block IKAR HWS with Galvanized Wire

### Blueprint



### Technical data

Part code	Code	Max. number of persons	Length m	Max load kg	L mm	B mm	T mm	Weight kg
822100600620	41-HWS 6	1	6	136	400	145	80	3
822100900620	41-HWS 9	1	9	136	455	160	85	3.7
822101200620	41-HWS 12	1	12	136	490	190	95	5.4
822101800620	41-HWS 18	1	18	136	540	220	97	6.9
822102400620	41-HWS 24	1	24	136	575	250	97	8.4