



Fall Arrest Block IKAR HWS with Galvanized Wire

Product information

Robust, low-maintenance fall arrest device with galvanized wire and swivel. The swivel prevents the wire from twisting. Internal energy-absorber and hook with fall indicator.

Low weight and maintenance thanks to extra light aluminium housing.

Approved for vertical and horizontal use.

Edge tested: Tested at sharp edges, $R \geq 0,5$ mm (CNB/P/11.060 2008 sharp edge Type A)

Carabiner: IKAR IKV21 (Lk = 186mm) small swivel snap hook (opening \varnothing 26 mm)

Can be delivered with other carabiners or scaffolding hooks up on request.

The blocks can be delivered with the following approvals: ANSI/ASSE Z 359.14-2014/LE up on request.

Material: Body: Aluminium

Marking: According to standard, CE-marked

Temperature range: -40°C up to +50°C.

Finish: Blue painted

Standard: EN 360

| Part code | Code | Max. number of persons | Length m | Max load kg | L | B mm | T mm | Weight kg |
|--------------|-----------|------------------------|----------|-------------|-----|------|------|-----------|
| 822100600620 | 41-HWS 6 | 1 | 6 | 136 | 400 | 145 | 80 | 3 |
| 822100900620 | 41-HWS 9 | 1 | 9 | 136 | 455 | 160 | 85 | 3.7 |
| 822101200620 | 41-HWS 12 | 1 | 12 | 136 | 490 | 190 | 95 | 5.4 |
| 822101800620 | 41-HWS 18 | 1 | 18 | 136 | 540 | 220 | 97 | 6.9 |
| 822102400620 | 41-HWS 24 | 1 | 24 | 136 | 575 | 250 | 97 | 8.4 |

Blueprint

