

D Shackle 316 Stainless



Product information



Design: Stainless steel D shackle, with pin. Good for lifting applications where a high level of corrosion resistance is required. Typical applications: Water utility installations & other corrosive facilities, Pump chains and pump lifting, Chemical installations - Chlorine plants etc, General lifting in off-shore applications, General lifting and tethering in leisure marine applications, General lifting purposes.

Proof load: 2x WLL

Material: Stainless Steel EN10088 1.4404 (Marine Grade 316L)

Marking: WLL, CE, Supplier,

Finish: Polished

Safety factor: : 6:1

Part Code	WLL ton	P mm	B mm	J mm	L mm	Weight kg
11.39D04TA	0.13	4	4	8	16	0.01
11.39D05TA	0.2	5	5	10	20	0.01
11.39D06TA	0.33	6	6	13	25	0.02
11.39D08TA	0.5	8	8	16	32	0.05
11.39D10TA	0.8	9,5	9,5	19	38	0.1
11.39D11TA	1	11	11	22	44	0.15
11.39D12TA	1.25	12,7	12,7	26	52	0.24
11.39D16TA	1.66	16	14,3	29	58	0.45
11.39D19TA	2.33	19	16	32	64	0.59
11.39D22TA	3.5	22,2	19	38	76	1
11.39D25TA	4.5	25,4	22,2	44	88	1.9
11.39D28TA	5.5	28,6	25,4	51	102	2.9
11.39D32TA	6.5	31,8	28,6	57	114	3.1
11.39D35TA	7.5	34,9	31,8	64	128	4.35
11.39D38TA	9	38	34,9	70	140	5.3

Blueprint

