

D Shackle 316 Stainless

Product information



Design: Stainless steel D shackle, with pin. Good for lifting applications where a high level of corrosion resistance is required. Typical applications: Water utility installations & other corrosive facilities, Pump chains and pump lifting, Chemical installations - Chlorine plants etc, General lifting in off-shore applications, General lifting and tethering in leisure marine applications, General lifting purposes.

Proof load: 2x WLL

[... Read more](#)

Material: Stainless Steel EN10088 1.4404 (Marine Grade 316L)

Marking: According to standard, CE-marked, WLL, Supplier


Finish: Polished

Standard: EN 10204

Safety factor: : 6:1

D Shackle 316 Stainless

Blueprint



Technical data

Part code	WLL ton	EWL mm	B mm	J mm	L mm	Pmm mm	Weight kg
420100010120	0.13	16	4	8	16	4	0.07
420100020120	0.2	20	5	10	20	5	0.013
420100030120	0.325	25	6	13	25	6	0.024
420100050120	0.5	32	8	16	32	8	0.053
420100080120	0.8	38	9,5	19	38	9,5	0.097
420100100120	1	44	11	22	44	11	0.152
420100130120	1.25	52	12,7	26	52	12,7	0.237
420100170120	1.66	58	14,3	29	58	16	0.45
420100230120	2.33	64	16	32	64	19	0.585
420100350120	3.5	76	19	38	76	22,2	1
420100450120	4.5	88	22,2	44	88	25,4	1.9
420100550120	5.5	102	25,4	51	102	28,6	2.9
420100650120	6.5	114	28,6	57	114	31,8	3.1
420100750120	7.5	128	31,8	64	128	34,9	4.35
420100900120	9	140	34,9	70	140	38	5.3