Lifting Solutions Group
Axel Johnson International

Bow Shackle 316 Stainless

Product information



Design: Stainless steel bow shackle, with pin. Good for lifting applications where a high level of corrosion resistance is required. Typical applications: Water utility installations & other corrosive facilities, Pump chains and pump lifting, Chemical installations - Chlorine plants etc, General lifting in off-shore applications, General lifting and tethering in leisure marine applications, General lifting purposes.

Proof load: 2x WLL

... *Read more*

Material: Stainless Steel EN10088 1.4404 (Marine Grade 316L)
Marking: CE-mark, WLL, Supplier,
Finish: Polished


Safety factor: 6:1

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Bow Shackle 316 Stainless

Blueprint



Technical data

Part code	WLL ton	EWL mm	B mm	J mm	L mm	P mm	W mm	Weight kg
420100010130	0.13	16	4	8	16	4	12	0.009
420100020130	0.2	22	5	10	22	5	16	0.014
420100030130	0.26	28	6	13	28	6	19	0.028
420100040130	0.4	35	8	16	35	8	25	0.059
420100060130	0.63	38	9.5	19	38	9.5	28	0.06
420100080130	0.8	46	11	22	46	11	33	0.161
420100100130	1	52	12.7	26	52	12.7	38	0.27
420100130130	1.33	60	14.3	29	60	16	43	0.5
420100200130	2	68	16	32	68	19	50	0.63
420100280130	2.75	76	19	38	76	22.2	57	1.05
420100380130	3.75	88	22.2	44	88	25.4	66	1.995
420100450130	4.5	102	25.4	51	102	28.6	76	3.045
420100550130	5.5	114	28.6	57	114	31.8	86	3.255
420100650130	6.5	128	31.8	64	128	34.9	95	4.568
420100750130	7.5	140	34.9	70	140	38	105	5.565

© November 2026 - All Rights Reserved