

## Automatic Elibia Hook

---

### Product information

Auto crane hook, allows you to remotely attach and release loads with no handling. It catches the masterlink with a magnet, a sensor indicates when the ring is in the right position, and a reinforced safety latch keeps the load safely attached during lifting.

10 and 20 tons are available in a Compact version (C)

[... Read more](#)



---


**Material:** Body: WELDOX® high strength steel body.

**Temperature range:** -20°C up to +85°C.

**Safety factor:** 4:1

## Automatic Elibia Hook

### Blueprint



### Technical data

| Part code    | WLL ton | Model | Max. releasable weight kg | A mm | B mm  | C mm  | D mm | E mm  | F mm | G mm  | H mm | I mm | J mm | K mm | L mm  | M mm | Weight kg |
|--------------|---------|-------|---------------------------|------|-------|-------|------|-------|------|-------|------|------|------|------|-------|------|-----------|
| 420500200080 | 2       | evo2  | 20                        | 188  | 131.5 | 269.3 | 22   | 120.9 | 42.5 | 28.8  | 26.7 | 21.3 | 11   | -    | -     | -    | 7         |
| 420500500080 | 5       | evo5  | 15-30                     | 277  | 170   | 469   | 409  | 194   | 43   | 49    | 57.6 | 25   | 41   | 58   | 350   | 15   | 26        |
| 420501000080 | 10      | evo10 | 20                        | 342  | 182.3 | 584   | 485  | 246   | 66   | 68    | 83   | 42   | 72   | 82   | 400,4 | 22   | 36        |
| 420502000080 | 20      | evo20 | 20                        | 341  | 182.3 | 663   | 553  | 246   | 66   | 105   | 83   | 42   | 72   | 115  | 480   | 29   | 43        |
| 420502500080 | 25      | evo25 | 20                        | 341  | 182.3 | 735   | 618  | 246   | 66   | 138.5 | 83   | 42   | 72   | 133  | 550   | 34   | 48        |