

## Rope Pulling Clamp

### Product information



These wire grips are the ideal tool to safely tensioning of copper and steel cables. They have a wide range of applications in manufacturing, agriculture and bridge construction. The profile of the clamping jaws is specifically designed for copper and steel cables so that the stretched material does not become damaged.

- Universal application: long, parallel tension clamping jaws made out of hardened and high-grade steel
- Corrosion protection: galvanized and burnished components
- Extremely durable and long-lasting: reliable, sophisticated process of cold-forming technology for the manufacturing of the jaws
- Easy handling: ergonomic
- Remote release possible: hole in clamping jaw
- Self-acting holding: spring effect on the tensioned cable
- Slip-resistant holding of the cable even at maximum traction

**Note:** With a tensile strength of 700N/mm<sup>2</sup>



Part Code	Rope Ø range mm	MBL ton	Stay rope mm <sup>2</sup>	Eye size mm	Capacity ton	Weight kg
10.4012504	1-5	1.25	1-16	20	0.5	0.25
10.4012511	3-9	2.5	6-35	22	1	0.85
10.4012528	4-12	4.5	16-70	27	1.7	1.27
10.4012535	6-18	7	50-150	25x38	3	1.83
10.4012542	10-28	8	90-400	30x40	3.5	4
10.4012559	20-40	9	240-800	30x40	4	6