

Female Swivel eye bolt Codipro FE SEB UP

Product information



The SEB lifting eye nut is a single swivel ring. Equipped with 2 pins that always guide it perfectly in the direction of the sling. It is specially designed for lifting, including rotating loads.

Features:

- Gradup steel ring that has a rotating range of 360°.
- Swivelling under load.
- Safe alternative to C15 DIN 580 eye nuts.
- Torque key adaptor available on request.

Material: High tensile steel

Marking: According to standard, CE-marked

Temperature range: -20°C up to +200°C

Standard: EN 1677-1

except grade/WLL

Safety factor: 5:1

Part code	WLL ton	Thread	Torque Nm	A mm	B mm	C mm	D mm	L max. mm	Weight kg
4215FESEBM8UP	0.4	M 8 (x1,25)	6	38	45	88	80	22	0.8
4215FESEBM10UP	0.5	M 10 (x1,50)	10	38	45	88	80	22	0.8
4215FESEBM12UP	0.8	M 12 (x1,75)	15	38	45	88	80	22	0.8
4215FESEBM16UP	1.4	M 16 (x2)	50	38	45	88	80	22	0.8
4215FESEBM20UP	2	M 20 (x2,5)	100	55	70	115	106	35	2.5
4215FESEBM24UP	3.4	M 24 (x3)	160	77	94	168	155	48	6.3
4215FESEBM30UP	5.5	M 30 (x3,5)	250	77	94	168	155	48	6.3
4215FESEBM36UP	9	M 36 (x4)	320	77	94	168	155	48	6.3

Technical data

5:1

METRIC THREADS

Torque (Nm)	1		2		2			3 → 4		
	0°	0°	0°	0°	0° → 45°	45° → 60°	Asymmetric	0° → 45°	45° → 60°	Asymmetric
6	0,70	1,40	0,40	0,80	0,56	0,40	0,40	0,84	0,60	0,40
10	1,20	2,40	0,50	1,00	0,70	0,50	0,50	1,05	0,75	0,50
15	1,70	3,40	0,80	1,60	1,12	0,80	0,80	1,68	1,20	0,80
50	3,20	6,40	1,40	2,80	1,96	1,40	1,40	2,94	2,10	1,40
100	5,00	10,00	2,00	4,00	2,80	2,00	2,00	4,20	3,00	2,00
160	6,30	12,60	3,20	6,40	4,48	3,20	3,20	6,72	4,80	3,20
160	7,00	14,00	3,40	6,80	4,76	3,40	3,40	7,14	5,10	3,40
250	8,50	17,00	5,50	11,00	7,70	5,50	5,50	11,55	8,25	5,50
320	12,00	24,00	9,00	18,00	12,60	9,00	9,00	18,90	13,50	9,00
400	12,00	24,00	12,00	24,00	16,80	12,00	12,00	25,20	18,00	12,00
600	15,00	30,00	15,00	30,00	21,00	15,00	15,00	31,50	22,50	15,00

max. load in t

Blueprint

