



## Double Swivel Ring Codipro SS DSR

### Product information



Stainless Steel Double Swivel Ring: SS DSR.  
Double articulation allows it to line up perfectly with the sling.  
From M8 to M30 as standard; for loads from 0.3 t to 3 t.

#### Features:

- Rotatable under load.
- Two ways of tightening:- Allen key or Torque wrench(also for external hex)

**Material:** AISI 316 L

**Marking:** According to standard, CE-marked

**Temperature range:** -20°C up to + 200°C

**Standard:** EN 1677-1

*except grade/WLL*

**Safety factor:** 5:1

Part Code	WLL ton	Thread	Torque Nm	StandardL1 mm	S1 mm	S2 mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	Weight kg
11.49SS.DSR M 6	0.1	M 6 (x1)	4	13	8	16	32	30	30	39	28	13	53	9,5	0.3
11.49SS.DSR M 8	0.3	M 8 (x1.25)	6	16	8	16	32	30	30	39	28	13	53	9,5	0.3
11.49SS.DSR M 10	0.5	M 10 (x1.50)	10	16	8	16	32	30	30	39	28	13	53	9,5	0.3
11.49SS.DSR M 12	0.8	M 12 (x1.75)	15	19	8	16	32	30	30	39	28	13	53	9,5	0.3
11.49SS.DSR M 14	1	M 14 (x2)	30	29	8	20	44	40	45	53	38	17	76	13	0.9
11.49SS.DSR M 16	1.4	M 16 (x2)	50	26	8	20	44	40	45	53	38	17	76	13	0.9
11.49SS.DSR M 18	1.4	M 18 (x2.5)	70	30	8	20	44	40	45	53	38	17	76	13	1
11.49SS.DSR M 20	1.4	M 20 (x2.5)	100	30	8	20	44	40	45	53	38	17	76	13	1
11.49SS.DSR M 22	2.2	M 22 (x2.5)	120	42	14	24	62	55	58	83	56	25	115	19	2.5
11.49SS.DSR M 24	2.7	M 24 (x3)	160	42	14	24	62	55	58	83	56	25	115	19	2.6
11.49SS.DSR M 27	2.8	M 27 (x3)	200	42	14	24	62	55	58	83	56	25	115	19	2.7
11.49SS.DSR M 30	3	M 30 (x3,5)	250	47	14	24	62	55	58	83	56	25	115	19	2.8

# Blueprint

