

## Female Double Swivel Shackle Codipro SS FE DSS



### Product information



Stainless steel female double swivel shackle SS FE DSS

**Design:** Centered lifting ring with double articulation except for the SEB, swivel eyebolt 360°.

**Material:** AISI 316 L

**Marking:** According to standard, CE-marked, The compliance to EC directives, GRADUP steel quality, The recommended tightening torque, The manufacturer brand, Traceability marks of each component (Blacksmith + batch number), The thread

**Temperature range:** -20°C up to + 200°C

**Finish:** An anti-corrosion coating on the unpainted parts of the CODIPRO swivel lifting points and orange color (RAL 2002) for the shackle.

**Standard:** EN 1677-1

*except grade/WLL*

**Safety factor:** 5:1

Part Code	WLL ton	Thread	Torque Nm	L max. mm	S mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	Weight kg
11.39SS.FE.DSS M 24	2.7	M 24 (x3)	160	66	50	66	31	70	98	73	149	30	5.8
11.39SS.FE.DSS M 30	3.5	M 30 (x3.5)	250	66	50	66	31	70	98	73	149	30	5.8
11.39SS.FE.DSS M 33	3.5	M 33 (x3.5)	250	66	50	66	31	70	98	73	149	30	5.8
11.39SS.FE.DSS M 36	5	M 36 (x4)	320	66	50	66	31	70	98	73	149	30	5.8

# Blueprint

