



## Spreader - Type 6650

### Product information



**General:** The spreaders have a high point of oscillation which results in good balance. The table only shows a few examples of available sizes and provide an indication of dimensions, loads and weights. Other lengths and working loads can be manufactured to suit a customers requirements. All spreaders are supplied complete with 2-leg sling and shackles according to the table. The beams can be provided with other accessories such as hooks, wire rope slings, chain slings or textile slings. Please also refer to our description in the introduction to this section on lifting beams.

**Design:** Lightweight welded pipe beam construction providing good torsional stiffness.

**Proof:** 1,5 x WLL.

**Material:** Hollow beam and plate manufactured with high-strength structural steel.

**Marking:** Working load limit and CE marking.

**Finish:** Yellow painted.

Part code	Length m	WLL t
62056650020XXX	1-6	2
62056650040XXX	1-6	4
62056650060XXX	1-6	5
62056650100XXX	1-6	10
62056650150XXX	1-6	15
62056650200XXX	1-6	20
62056650250XXX	1-6	25
62056650YYYYXX	1-6	>25 Ton

Technical data

Art No	WLL	Length	Shackle number
	tons	m	
13.356650020	2	1-6	11.311019470
13.356650040	4	1-6	11.311019472
13.356650060	6	1-6	11.311019490
13.356650100	10	1-6	11.311019533
13.356650150	15	1-6	11.311019551
13.356650200	20	1-6	11.311019597
13.356650250	25	1-6	11.311019613

## Blueprint

