

Wedge Socket 3000

Product information



General: Intended for attaching of wire rope where switching often occur, e.g. blocks of mobilecranes, or to be able to adjust the length of the wire rope. See recommended assembly to get correct results.

Design: Bended and welded house made of plate. Wedge made of plate with milled groove and symmetrical shaped to avoid error assemblies. Turned bolt with head, low nut and split cotter. The wedge sockets is delivered complete. Note that some wedge houses fit to different sizes of wedges.

Marking house and wedge: Dimension area.

Proof: Batch proof 2 x WLL.

Material: House, wedge and bolt by high-tensile construction steel.

Finish: Electro-zink plated

Note: To elevators and mines we recommend other designs.

Safety factor: 5:1

Part Code	Code	Rope diameter mm	WLL ton	MBL T	Finish	A mm	B mm	E mm	G mm	L mm	D mm	Weight kg
10.20300109	3001A	8-9	2	10	Electro galvanized/Zinc plated	30	16	29	70	145	27,5	1.3
10.20300110	3001B	10	2	10	Electro galvanized/Zinc plated	30	16	29	70	145	27,5	1.2
10.20300112	3001C	11-12	2	10	Electro galvanized/Zinc plated	30	16	29	70	145	27,5	1.2
10.20300414	3004A	13-14	5	25	Electro galvanized/Zinc plated	60	34	44	96	216	31,5	4.6
10.20300417	3004B	15-17	5	25	Electro galvanized/Zinc plated	60	34	44	96	216	31,5	4.4
10.20300519	3005A	18-19	6	30	Electro galvanized/Zinc plated	66	40	50	110	245	39,5	6.2
10.20300623	3006A	20-23	9	45	Electro galvanized/Zinc plated	72	40	50	120	280	39,5	8.7
10.20300728	3007A	24-28	12	60	Electro galvanized/Zinc plated	75	42	67	140	327	43,5	13
10.20300832	3008A	29-32	20	100	Electro galvanized/Zinc plated	104	60	75	245	555	65	40
10.20300836	3008B	33-36	20	100	Electro galvanized/Zinc plated	104	60	75	245	555	65	39
10.20300940	3009A	37-40	27	135	Electro galvanized/Zinc plated	124	80	95	270	675	79	65
10.20300944	3009B	41-44	27	135	Electro galvanized/Zinc plated	124	80	95	270	675	79	63

Blueprint

