

Swivel Hook Crosby S-1326

Product information



The S-1326 hook is a positioning device and is not intended to rotate under load.

Features:

- Individually Proof Tested at 2-1/2 times the 4:1 Working Load Limit with certification.
- Recessed trigger design is flush with the hook body, protecting the trigger from potential damage.
- Easy to operate with enlarged thumb access.
- Positive Lock Latch is Self-Locking when hook is loaded.
- Rated for both Wire Rope and use with Grade 80/100 Chain.

... [Read more](#)

Material: Forged Alloy Steel - Quenched and Tempered.


Finish: Painted

Safety factor: 4:1

Grade: 10

Swivel Hook Crosby S-1326

Blueprint



Technical data

Part code	Chain diameter	WLL ton	A mm	B mm	C mm	D mm	E mm	F mm	H mm	J mm	L mm	AA**mm mm	Weight kg
402300151400	6	1.45	38.1	33.5	156	20.1	66	17	12.7	16	28.7	38.1	0.57
402300261400	7-8	2.6	44.5	40.4	193	27.9	88.9	22.1	16	20.6	35.1	51	1.18
402300401400	10	4	50.8	43.9	224	29.7	112	27.9	19.1	23.9	44.5	63.5	2.13
402300681400	13	6.8	63.5	60.5	284	42.4	139	32	25.4	29.5	53.6	76.2	3.92
402301031400	16	10.3	69.9	64.3	328	51.8	167	38.1	28.7	38.1	63.2	89	7.71
402301601400	18-20	16	71.9	64	358	56.4	197	51.1	27.9	51.6	89.4	127	10.9
402302001400	22	20	87.4	81	417	62.2	222	57.4	33	55.9	97.3	152	13.2