



Lifting Eye FP Grade 100

Product information



MORE THAN CHAIN

General: Enormously flat lifting eye. The eyes can be loaded with working load limit in all directions and rotates 360°. Automatic locking link when folded.

Material: Eye and swivel of alloy steel.

Marking: WLL.

Finish: Painted.

Note: The surface that the lifting eyes shall be attached to shall be flat and tolerate the load it is going to be exposed to.




Safety factor: 4:1

Grade: 10

Part Code	Code	WLL ton	Thread	Tightening torque	a mm	b mm	c mm	d mm	e mm	f mm	g mm	l mm	Øs mm	Weight kg
11.420381100000	FP-0,5	0.5	M10	40	69	50	48	13	28	100	12	52	34	0.7
11.420381101000	FP-0,8	0.8	M12	65	69	50	48	13	28	100	17	51	34	0.71
11.420381101500	FP-1,5	1.5	M16	160	69	50	48	13	28	100	27	49	34	0.72
11.420381102000	FP-2,5	2.5	M20	250	69	50	48	13	33	103	37	44	41	0.73
11.420381104200	FP-4S	4	M24	300	69	50	48	13	34	103	46	40	41	0.76
11.420381104000	FP-4	4	M24	300	104	76	78	18	39	147	41	79	58	2.6
11.420381105000	FP-5	5	M27	400	104	76	78	18	39	147	51	72	58	2.7
11.420381106000	FP-6	6	M30	500	104	76	78	18	39	147	51	70	58	2.8
11.420381108000	FP-8	8	M36	600	104	76	78	18	43	147	57	62	58	2.8

Technical data

WLL (ton)

			
FP-0,5	0.7	0.5	0.7
FP-0,8	1.25	0.8	1.12
FP-1,5	2.12	1.5	2
FP-2,5	3.55	2.5	3.35
FP-4S	4	4	5.6
FP-4	5.6	4	5.6
FP-5	7.1	5.3	7.1
FP-6	8	6	8
FP-8	8	8	11.2

Blueprint

