Lifting Solutions Group
Axel Johnson International

Lifting Eye TP

Product information



The THEIPA Point is a rotatable attachment swivel with ball bearing for industrial lifting and load handling applications. It is designed to provide controlled swivel movement under load while helping reduce link kinking during lifting operations. The galvanized construction supports corrosion resistance in demanding industrial environments.

Best used for:

- Rotating lifting applications requiring controlled load alignment.
- Industrial environments exposed to moisture or corrosion risk.

Product benefits:

- Ball bearing enables smooth rotation under load.
- Crimped link design helps prevent link kinking.
- Galvanized finish improves corrosion resistance.
- Multiple thread sizes support varied lifting configurations.
- RFID chip option supports traceability and inspection processes.

... *Read more*

Material: Eye and swivel of alloy steel
Marking: CE-mark, UKCA-marked, WLL
Temperature range: -40° up to +400°C
Finish: Galvanized coating - Paint
Note: The surface that the lifting eyes shall be attatched to shall be flat and tolerate the load it is going to be exposed to.


Safety factor: 4:1

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Lifting Eye TP

Blueprint



Technical data

Part code	Code	WLL ton	Thread mm	Tightening torque Nm	Pitch DIN 13	b mm	bi mm	d mm	e mm	g mm	SW mm	t mm	t1 mm mm	ø mm mm	Weight kg
42150381400001	TP 0.7	0.5	M 10 x 18	40	1.5	36.5	32	M 10	18	48	34	41	55	13	0.42
42150381401000	TP 1.4	1.4	M 16 x 20	130	2	36.5	32	M 16	20	48	34	41	55	13	0.43
42150381402000	TP 2.5	2.5	M 20 x 30	170	2.5	52	34	M 20	30	68	46	57	70	16	0.95
42150381404000	TP 4	4	M 24 x 30	280	3	57	45	M 24	30	75	50	63	85	18	1.43
42150381406000	TP 6.7	6.7	M 30 x 35	400	3.5	70	45	M 30	35	95	65	78	86	20	2.33
42150381408000	TP 8	8	M 30 x 35	600	3.5	81	60	M 30	35	106	75	86	115	23	3.59
42150381410000	TP 10	10	M 36 x 50	600	4	81	60	M 36	50	106	75	86	115	23	3.72
42150381412003	TP 12.5	12.5	M 42 x 50	700	4.5	81	60	M 42	50	106	75	86	115	23	3.82
42150381417003	TP 17	13	M 42 x 60	800	4.5	104	70	M 42	60	127	95	106	140	30	7.34
42150381420000	TP 20	20	M 64 x 96	900	6	104	70	M 64	96	127	95	106	140	30	8.85
42150381428000	TP 28	28	M 64 x 96	1,000	6	129	80	M 64	96	174	115	135	170	35	16.3
42150381435000	TP 35	35	M 80 x 120	1,400	6	148	100	M 80	120	187	135	146	220	43	25.1
42150381440002	TP 40	40	M 80 x 120	1,500	6	170	110	M 80	120	233	150	182	240	46	35.5

© November 2026 - All Rights Reserved