

## Chain Sling CSX-265 Grade 10

---

### Product information



**Design:** Chain sling with master link and shortening hooks on one end and clevis load hook on the other end of each leg.

From  $\varnothing 19$  up to 26mm chain fitted with other type shortening hook and  $\varnothing 26$  mm chain is fitted with an eye hook. Other combinations possible on demand.

**Dimension:**  $\varnothing 6$ –26 mm.

[... Read more](#)

**Material:** Alloy steel.

**Marking:** According to standard, CE-marked

**Temperature range:**  $-40^{\circ}\text{C}$  up to  $200^{\circ}\text{C}$  (up to  $380^{\circ}$  possible on demand)

**Standard:** EN 818-4

**Warning:** Not to be heat-treated.

**Safety factor:** 4:1

**Grade:** 10

## Chain Sling CSX-265 Grade 10

### Technical data

| Part code       | Chain diameter<br>mm | WLL<br>ton |
|-----------------|----------------------|------------|
| 240800600000120 | 6                    | 2          |
| 240800700000120 | 7                    | 2.65       |
| 240800800000120 | 8                    | 3.55       |
| 240801000000120 | 10                   | 5.6        |
| 240801300000120 | 13                   | 9.5        |
| 240801600000120 | 16                   | 14         |