

Load Hook HS/S Grade 10 - Eye/Latch

Product information



Eye Load hook - Sling hook with safety latch for general lifting applications... [Read more](#)

Material: Alloy steel.

Marking: According to standard, CE-marked

Temperature range: -40°C up to 380°C

Finish: Violet powder coated.

Standard: EN 1677-2 (+25% WLL)


Warning: Not to be heat-treated.

Safety factor: 4:1

Grade: 10

Load Hook HS/S Grade 10 - Eye/Latch

Blueprint



Technical data

| Part code | Code | Chain diameter mm | WLL ton | EWL mm | a mm | b mm | d1 mm | d2 mm | e mm | g1mm mm | h mm | Weight kg |
|--------------|---------------|-------------------|---------|--------|------|------|-------|-------|------|---------|------|-----------|
| 402300140420 | HS/S-6-10 | 6 | 1.4 | 85 | 17 | 68 | 20 | 10 | 85 | 19 | 21 | 0.29 |
| 402300250420 | HS/S-7/8-10 | 7-8 | 2.5 | 106 | 19 | 88 | 25 | 11 | 106 | 26 | 27 | 0.57 |
| 402300400420 | HS/S-10-10 | 10 | 4 | 131 | 26 | 109 | 34 | 16 | 131 | 31 | 33 | 1.19 |
| 402300670420 | HS/S-13-10 | 13 | 6.7 | 164 | 33 | 134 | 43 | 19 | 164 | 39 | 44 | 1.96 |
| 402301000420 | HS/S-16-10 | 16 | 10 | 183 | 40 | 155 | 50 | 25 | 183 | 45 | 50 | 3.85 |
| 402301600420 | HS/S-19/20-10 | 19 | 16 | 205 | 48 | 178 | 55 | 27 | 205 | 53 | 55 | 5.92 |
| 402301900420 | HS/S-22-10 | 22 | 19 | 225 | 50 | 196 | 60 | 29 | 225 | 62 | 62 | 7.65 |
| 402302650420 | HS/S-26-10 | 26 | 26.5 | 259 | 70 | 235 | 70 | 37 | 259 | 73 | 75 | 12.76 |