

Load Hook HS/S Grade 10 - Eye/Latch



Product information

General: Eye Load hook - Sling hook with safety latch for general lifting applications.

Material: Alloy steel.

Marking: According to standard, CE-marked

Temperature range: -40°C up to 380°C

Standard: EN 1677-1

Warning: Not to be heat-treated.

Safety factor: 4:1

Grade: 10

Part Code	Code	Chain diameter mm	WLL ton	e mm	h mm	a mm	d1 mm	d2 mm	g1 mm	b mm	Weight kg
11.1169952	HS/S-6-10	6	1.4	85	21	17	20	10	19	68	0.29
11.1169958	HS/S-7/8-10	7-8	2.5	106	27	19	25	11	26	88	0.57
11.1169953	HS/S-10-10	10	4	131	33	26	34	16	31	109	1.19
11.1169954	HS/S-13-10	13	6.7	164	44	33	43	19	39	134	1.96
11.1169955	HS/S-16-10	16	10	183	50	40	50	25	45	155	3.85
11.1169950	HS/S-19/20-10	19	16	205	55	48	55	27	53	178	5.92
11.1169956	HS/S-22-10	22	19	225	62	50	60	29	62	196	7.65
11.1113409	HS/S-26-10	26	26.5	259	75	70	70	37	73	235	12.76

Blueprint

