



## 4 Special Clevis Sub-Assembly GTVK/SUN

### Product information



**General:** For 3 and 4-leg slings with shortening element.

**Temperature range:** -40 °C to 200 °C

**Safety factor:** 4:1.

**Grade:** 12

| Part Code       | Code          | WLL ton | chain Ø mm | WLL 45-60° ton | Chain Ø inch | can be used with single hook acc. DIN15401 up to nr. | d mm | t mm | w mm | e mm | Weight kg |
|-----------------|---------------|---------|------------|----------------|--------------|--|------|------|------|------|-----------|
| 11.03KWB4016032 | GTVK/SUN 4-7  | 5       | 7          | 3.55           | 9/32         | 10   | 27   | 190  | 110  | 368  | 6.45      |
| 11.03KWB4016039 | GTVK/SUN 4-8  | 6.3     | 8          | 4.5            | 5/16         | 10   | 27   | 190  | 110  | 368  | 6.45      |
| 11.03KWB4015967 | GTVK/SUN 4-10 | 10.6    | 10         | 7.5            | 3/8          | 12   | 30   | 190  | 110  | 433  | 11.7      |
| 11.03KWB4016011 | GTVK/SUN 4-13 | 17      | 13         | 11.8           | 1/2          | 12   | 38   | 275  | 150  | 616  | 23.84     |
| 11.03KWB4016012 | GTVK/SUN 4-16 | 25.6    | 16         | 18.3           | 5/8          | 12   | 38   | 275  | 150  | 658  | 36.16     |

Blueprint

