Lifting Solutions Group
Axel Johnson International

The Original Roundsling Extreema® with Dyneema® core

Product information



The Original Extreema® roundsling with Dyneema® core is a high-strength lifting sling designed for heavy-duty industrial lifting where low weight and durability are critical. Built with parallel-laid HMPE fibers, it delivers consistent load distribution and reliable performance. The HMPE cut-resistant sleeve protects the sling and load in demanding handling conditions.

Its core is made of Bio-Based Dyneema®, which makes it up to 15 times stronger than steel on a weight-to-weight basis.

The sleeve is white HMPE Extreema® L-series sleeve. With exceptional performance against cuts, abrasions, and punctures. The white sleeve is repairable.

WLL range: 3t – 600t
EWL range: 0,5m – 65m

When to choose this product

Best for:

- Heavy lifting requiring high strength with minimal sling weight
- Environments with abrasion, cutting risk, or chemical exposure

Product benefits:

- Dyneema® HMPE core provides high strength with low weight
- Cut-resistant HMPE sleeve protects against abrasion and punctures
- Does not absorb water and floats, suitable for marine use
- Chemical-resistant material supports use in harsh environments
- Repairable sleeve extends service life and reduces downtime
- RFID improve inspection and traceability

... *Read more*

Material: Core: Bio based Dyneema® - Sleeve: HMPE
Marking: CE-mark
Temperature range: -50°C up to +70°C

Safety factor: 7:1

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

The Original Roundsling Extreema® with Dyneema® core

Technical data

Part code	Code	WLL ton
34050100XXX0010	EXL/10/XXX	10
34050120XXX0010	EXL/12/XXX	12
34050150XXX0010	EXL/15/XXX	15
34050200XXX0010	EXL/20/XXX	20
34050250XXX0010	EXL/25/XXX	25
34050300XXX0010	EXL/30/XXX	30
34050400XXX0010	EXL/40/XXX	40
34050500XXX0010	EXL/50/XXX	50
34050750XXX0010	EXL/75/XXX	75
34051000XXX0010	EXL/100/XXX	100
34051250XXX0010	EXL/125/XXX	125
34051500XXX0010	EXL/150/XXX	150
34052000XXX0010	EXL/200/XXX	200

© November 2026 - All Rights Reserved