

## Winner 200 Chain Pewag

### Product information



Round steel chains for use in lifting or lashing chains.

**Material:** High duty chain.

**Marking:** According to standard, Each chain link is marked with 10 for grade 10 and the chain is marked pewag 10 (PWA 100).

**Temperature range:** -40°C up to +200°C.

**Finish:** Blasted, clear painted.

**Standard:** EN 818-2

**Safety factor:** 4:1

**Grade:** 10

Part Code	Chain diameter mm	WLL ton	Min. breaking force kN	Std. length m	dn mm	t mm	b1 mm	b2 mm	Weight kg/m
11.6532264	5	1	39.3	100/50	5	16	7.5	18.5	0.61
11.653959	6	1.4	56.5	200/50	6	18	8.7	21.6	0.96
11.653973	7	1.9	77	300/250/50	7	21	9.5	25.2	1.2
11.653975	8	2.5	101	250/200/50/50	8	24	10.9	28.8	1.57
11.653976	10	4	157	150/130/50	10	30	13.5	37	2.46
11.653986	13	6.7	265	100/75/50	13	39	17.5	46.8	4.18
11.653988	16	10	402	100/50/25	16	48	21.5	57.6	6.28
11.653989	19	14	567	50/35/25	19	57	26.6	69.4	8.92
11.654043	22	19	760	30/25/LFM	22	66	29.5	79.2	11.88
11.6572801	26	26.5	1,006	25	26	78	35	94	16.18
11.6514245	32	40	1,610	20	32	96	43.2	115	24.1

# Blueprint

