



## Master Link Pewag AW

### Product information

AW Master links are designed for the assembly of chain slings. For pewag connex and welded system.

Master link for 1-leg chain AI.

Master link for 2-leg chain AII.

Master link for 3- and 4-leg chain AIII/IV - only with transition link BW as on VW.

Can also be used as end link A I

**Material:** High duty

**Marking:** According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type.

**Temperature range:** -40°C up to +380°C.

**Finish:** Orange powder coated.

**Standard:** EN 1677-4

**Safety factor:** 4:1

**Grade:** 10

Part Code	Code	WLL ton	LC kN	For chain Ø 1-leg AW I mm	For chain Ø 2-leg AW II mm	Single hook DIN 15401 no.	Double hook DIN 15402 no.	d mm	s mm	t mm	w mm	Weight kg
11.0246774	AW 10	1.4	28	5	5	1.6	2.5	10	10	80	50	0.14
11.0246775	AW 13	2.3	46	6+7	6	2.5	4	13	10	110	60	0.34
11.0246776	AW 16	3.5	70	8	7	2.5	4	16	14	110	60	0.53
11.0246777	AW 18	5	100	10	8	5	6	19	14	135	75	0.92
11.0246778	AW 22	7.6	152	13	10	6	8	23	17	160	90	1.6
11.0246779	AW 26	10	200	16	13	8	10	27	20	180	100	2.46
11.0246780	AW 32	14	280	19	16	10	12	33	26	200	110	4.14
11.0246781	AW 36	25.1	502	22	19	16	20	36	29	260	140	6.22
11.0246782	AW 45	30.8	616	26	22	25	32	45	-	340	180	12.82
11.0260723	AW 50	40	800	32	26	32	40	50	43	350	190	16.55
11.0271783	AW 56	64	1,277	-	32	32	40	56	-	400	200	27.01
11.0254786	AW 72	85	1,700	-	-	50	63	70	-	460	250	45.3

# Blueprint

