



## Connex Connecting Link Pewag CW

### Product information

CW Connex connecting link for pewag connex system.

Load pin and collar CBH are also separately available.

Connecting link for:

Master link - chain, chain - chain, hook - chain.

Only for straight pull.

**Material:** High duty grade 10.

**Marking:** According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type.

**Temperature range:** -40°C up to +380°C.

**Finish:** Orange powder coated.

**Standard:** EN 1677-1

**Safety factor:** 4:1

**Grade:** 10

Part Code	Code	WLL ton	LC kN	b mm	c mm	d mm	e mm	g mm	s mm	t mm	Weight kg
11.064757	CW 5	1	20	34	7	7	38	13	9	12	0.06
11.064457	CW 6	1.4	28	39	8	8	44	14	11	13	0.08
11.062823	CW 7	1.9	36	46	10	9	53	17	13	16	0.14
11.0689347	CW 8	2.5	50	55	12	10	62	19	14	20	0.24
11.0689340	CW 10	4	80	64	15	13	72	24	18	22	0.42
11.062693	CW 13	6.7	134	79	20	17	88	28	22	26	0.85
11.0690112	CW 16	10	200	105	24	24	112	34	29	35	1.9
11.0690085	CW 19/20	16	320	123	32	25	126	42	35	45	3.1
11.0690041	CW 22	19	380	148	36	26	157	51	39	46	4.6
11.0689021	CW 26	26.5	530	175	40	30	190	60	46	49	6.8
11.0689023	CW 32	40	800	216	47	35	206	80	56	63	11.2

# Blueprint

