



Clevis Sling Hook Pewag KHSW

Product information

KHSW Clevis sling hooks are designed for the assembly of chain slings.
General purpose hook, can be used without transition link and without connecting link.
With forged safety catch.

Material: High duty grade 10.

Marking: According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type.

Temperature range: -40°C up to +380°C.

Finish: Orange powder coated.

Standard: EN 1677-2

Safety factor: 4:1

Grade: 10

Part code	Code	WLL ton	LC kN	EWL	a mm	b mm	d mm	e mm	g1 mm	h mm	Weight kg
402300140550	KHSW 5/6	1.4	28	69	15	66	7	69	19	20	0.2
402300190550	KHSW 7	1.9	38	95	19	90	9	95	26	28	0.6
402300250550	KHSW 8	2.5	50	95	19	90	10	95	26	28	0.6
402300400550	KHSW 10	4	80	109	25	108	12	109	31	35	1.1
402300670550	KHSW 13	6.7	124	136	34	131	16	136	39	41	2
402301000550	KHSW 16	10	200	155	37	153	20	155	45	49	3.48
402301600550	KHSW 19/20	16	320	184	51	177	24	184	53	53	5
402301900550	KHSW 22	19	360	214	52	196	27	214	62	62	9

Blueprint

