



Grab Hook Pewag PW

Product information

Thanks to the special design of the chain contact area, this standard shortening hook ensures optimal interaction between chain and hook. Even when shortened, the load capacity is not reduced.

Material: High duty grade 10.

Marking: According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type.

Temperature range: -40°C up to +380°C.

Finish: Orange powder coated.

Standard: EN 1677-1

Safety factor: 4:1

Grade: 10

Part Code	Code	WLL ton	b mm	d1 mm	d2 mm	e mm	g mm	Weight kg
11.2150214	PW 5	1	40	11	9	47	7	0.13
11.2150229	PW 6	1.4	44	12	9	50	7	0.15
11.2150247	PW 7/8	2.5	57	16	12	65	9	0.37
11.2150237	PW 10	4	77	20	14	77	12	0.7
11.2150242	PW 13	6.7	92	26	19	101	15	1.56
11.2150243	PW 16	10	113	32	23	121	19	2.9
11.2160820	PW 19/20	16	150	36	27	151	25	6.15
11.2160821	PW 22	19	165	42	31	170	27	8.3
11.2170809	PW 26	26.5	195	50	37	201	32	13.8
11.2188710	PW 32	40	242	60	43	243	38	25

Blueprint

