

## Turnbuckle TR Series Jaw - Jaw



### Product information

**General:**

Closed body Turnbuckles jaw/jaw with trapezoid thread standard supplied with lock nuts.

**Features:**

- Standard painted blue, but can be supplied in any colour or galvanised.
- Available in all combinations of eyes, stud eyes and welding ends.
- Lock plates or special locking devices possible.
- Can be supplied with turning wheel or ratchet.
- Other sizes possible.

**Temperature range:** -40°C t/m +110° C at 100% capacity rating. Higher temperature possible with reduction of WLL.

**Warning:** Straight or in-line pull only.

**Safety factor:** 5:1

Part Code	WLL ton	Take up mm	Thread trap.	L min. mm	L max. mm	A mm	P mm	U mm	V mm	W mm	T mm	Weight kg
11.50410016011	1.6	167	22 X 5	398	565	240	20	55	22.5	23	11	3
11.50410020011	2	181	24 X 5	422	603	260	22	58	25	26	12	4
11.50410025011	2.5	215	28 X 5	512	727	280	24	73	27.5	30	12	6
11.50410031011	3.1	225	30 X 6	543	768	300	27	80	30	32	15	8
11.50410040011	4	232	32 X 6	584	816	320	30	86	32.5	35	15	10
11.50410050011	5	242	36 X 6	612	854	340	36	93	37.5	40	20	15
11.50410063011	6.3	270	44 X 7	701	971	380	39	108	42.5	45	20	20
11.50410080011	8	296	48 X 8	755	1,051	420	45	112	47.5	50	25	28
11.50410100011	10	306	52 X 8	798	1,104	460	48	115	55	60	25	35
11.50410126011	12.6	352	55 X 9	862	1,214	500	52	122	60	65	30	47
11.50410160011	16	366	65 X 10	944	1,310	540	60	130	65	70	30	62
11.50410200011	20	380	70 X 10	1,042	1,422	580	68	145	70	75	35	85
11.50410250011	25	402	75 X 10	1,126	1,528	620	72	160	75	80	35	100
11.50410315011	31.5	438	80 X 10	1,192	1,630	660	80	170	85	90	40	130
11.50410400011	40	464	90 X 10	1,280	1,744	695	90	190	92	100	45	175
11.50410500011	50	520	100 x 10	1,390	1,910	770	100	205	105	110	50	236
11.50410630011	63	564	110 X 10	1,526	2,090	855	110	220	112	120	60	325
11.50410800011	80	630	120 X 10	1,653	2,283	920	125	235	127	140	70	452
11.50411000011	100	720	130 X 10	1,748	2,468	995	140	250	142	156	70	577
11.50411250011	125	752	140 X 10	1,900	2,652	1,070	160	270	162	176	80	811
11.50411600011	160	880	160 X 10	2,090	2,970	1,220	180	290	182	200	90	1,120

# Blueprint

