

Silmukkapääte AISI 316

Tuotetiedot



Yleistä: Pääte puristetaan yksinkertaiseen teräsköyteen.

Rakenne: Kiillotettu

Materiaali: Ruostumaton haponkestävä teräs AISI 316.



Tuotekoodi	Köyden halkaisija mm	Murtolujuus t	A mm	B mm	D1 mm	D2 mm	L1 mm	L2 mm	Paino kg/100 kpl
10.07190002	2	1,2	3	12	5,5	5,5	41	24	0,9
10.07190025	2,5	1	3	12	5,5	5,5	44	27	0,8
10.07190003	3	1,3	4	14	6,35	6,5	60	38	1,3
10.07190004	4	1,7	5	17	7,5	8,5	67	45	2,3
10.07190005	5	2,4	6	21	9,0	10,5	79	51	3,9
10.07190006	6	5,5	8	25	12,58	13,0	94	64	8,7
10.07190006X	6	5,5	10	28	12,58	13,2	105	64	13,2
10.07190007	7	6,8	9	27	14,2	13,0	104	70	11,5
10.07190007X	7	6,8	10	28	14,2	13,2	110	70	13,5
10.07190008	8	8	10	30	16,0	14,5	124	83	17
10.07190008X	8	8	12	36	16,0	16,5	141	83	23,5
10.07190010	10	9,7	11	35	17,8	16,3	137	89	25
10.07190010X	10	9,7	16	40	17,8	19,5	165	100	38
10.07190012X	12	14,2	15	42	21,4	19,3	178	120	41
10.07190012	12	11,4	15	40	20,0	19,3	156	105	41,5
10.07190014	14	15,9	18	47	25,0	23,0	206	140	75,6
10.07190016	16	19	20	53	28,0	26	232	160	102
10.07190019	19	31	25	65	34,5	28,5	302	200	209
10.07190022	22	42	30	70	40,4	33,0	348	230	314
10.07190026	26	53	30	77	46,0	36,0	400	280	425

Mittakuva

